



Pago Oprolsystemen

sales@aben.eu

www.haspel.expert

-

Technische specificaties - Caractéristiques techniques - Technical specifications - Technische Daten

RHK-1050



|                               |             |
|-------------------------------|-------------|
| Description                   | cable reel  |
| Type of reel                  | Cable reel  |
| Number of contacts            | 3           |
| Conductor cross-section (mm²) | 1           |
| Length (m)                    | >0-5        |
| winding length cable max (m)  | 4           |
| Max Volt (V)                  | 230         |
| Max Amp (A)                   | 10          |
| Cable mounted                 | yes         |
| Cable Type                    | H05 VV-F    |
| Drive                         | spring      |
| Ratched Lock                  | yes         |
| IP Class                      | IP40        |
| Material                      | plastic     |
| Model                         | closed      |
| Power (wound up)-(Watt)       | 1250        |
| Power (unwound)-(Watt)        | 2300        |
| Temperture (°C)               | 5/35        |
| Application                   | industrial  |
| Thermic protection            | no          |
| overhang (m)                  |             |
| Cable guide                   | no          |
| Movement of reel              |             |
| Finishing                     |             |
| Color                         | orange      |
| Number of Cycle               | 30000       |
| External cable diameter (mm)  |             |
| Height(mm)                    | 224         |
| Width(mm)                     | 160         |
| Depth(mm)                     | 132         |
| Kg                            | 1.7         |
| Cable end                     | Schuko plug |
| Installation Position         |             |

RHK1050